



Sweeper hose, medium-heavy, exterior folds, very flexible



### Application

- municipal vehicle: sweeper, sweeping machine

### Properties

- medium-heavy duty
- highly flexible + compressible
- highly abrasion resistant
- protected, flow-optimizing exterior folds
- microbe resistant

- good resistance to oil, gasoline and chemicals
- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- -40° C to 90° C

### Design

- AIRDUC® profile hose

- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 1,0 mm approx.

### Delivery variants

- further diameters and lengths available on request
- transparent + partially black coloured (standard)
- special colours: partially coloured, completely coloured
- customer-specific branding

I.D. (in / mm)	outer Ø (mm)	Pressure (bar)	Vacuum (bar)	Bending Radius (mm)	Weight (kg/m)	Production Lengths (m)	Order No.
<b>transparent</b>							
5,5 / 140	149.00	0,495	0,085	94.00	1.55	5 10	351-0140-2040
6 / 150-152	159.00	0,460	0,075	100.00	1.75	5 10	351-0150-2040
6,3 / 160	169.00	0,435	0,065	106.00	1.95	5 10	351-0160-2040
- / 170	179.00	0,410	0,065	110.00	2.20	5 10	351-0170-2040
7 / 178-180	189.00	0,385	0,055	118.00	2.40	5 10	351-0180-2040
8 / 200-203	211.00	0,350	0,055	130.00	2.40	5 10	351-0200-2040
- / 250	259.00	0,280	0,020	160.00	2.95	5 10	351-0250-2040
<b>partially black coloured</b>							
5,5 / 140	149.00	0,495	0,085	94.00	1.55	5 10	351-0140-5200
6 / 150-152	159.00	0,460	0,075	100.00	1.75	5 10	351-0150-5200
6,3 / 160	169.00	0,435	0,065	106.00	1.95	5 10	351-0160-5200
- / 170	179.00	0,410	0,065	110.00	2.20	5 10	351-0170-5200
7 / 178-180	189.00	0,385	0,055	118.00	2.40	5 10	351-0180-5200
8 / 200-203	211.00	0,350	0,055	130.00	2.40	5 10	351-0200-5200
- / 250	259.00	0,280	0,020	160.00	2.95	5 10	351-0250-5200

## Accessories



CONNECT 240 + 241 AS



CLAMP 211



CONNECT 270-271