



Vacuum truck hose, heavy and reinforced, very flexible

### Application

- suction excavator
- municipal vehicle: sweeper, sweeping machine

### Properties

- heavy duty and reinforced
- highly abrasion resistant
- microbe resistant
- good resistance to oil, gasoline and chemicals
- very good low temperature flexibility

- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- -40 °C to 90 °C
- short time to 125 °C

### Design

- AIRDUC® profile hose
- spring steel wire firmly embedded in wall

- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 2,5 mm approx.
- reinforcement of the primary abrasion areas

### Delivery variants

- further diameters and lengths available on request
- orange (standard)
- special colours: transparent, full coloured
- customer-specific branding

| I.D.        | outer Ø | Pressure | Vacuum | Bending Radius | Weight | Dimensions in Stock | Order No.     |
|-------------|---------|----------|--------|----------------|--------|---------------------|---------------|
| (in / mm)   | (mm)    | (bar)    | (bar)  | (mm)           | (kg/m) | (m)                 |               |
| 8 / 200-203 | 213.00  | 0,600    | 0,120  | 316.00         | 5.13   | 5                   | 355-0200-5202 |
| 10 / 254    | 267.00  | 0,482    | 0,075  | 407.00         | 6.51   | 5                   | 355-0254-5202 |
| - / 352     | 365.00  | 0,340    | 0,050  | 554.00         | 9.03   | 5                   | 355-0352-5202 |

## Accessories



CLAMP 211



CONNECT 270-271



CONNECT 240 + 241 AS