

CLAMP 216



Hose Clamp for watertight attachment of heavy, externally corrugated spiral hoses

Properties

- watertight and tensile connection at very low overpressure due to special spiral geometry
- easily and quickly fitted
- re-usable

Design

- re-usable
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Design

- Quality: W2; clamp strip: stainless steel 1.4016 = AISI 430; clamp wire: stainless steel 1.4310 = AISI 301 (INOX); screw: chromated steel; Body: stainless steel 1.4016 = AISI 430

Delivery variants

- further diameters available on request

Suitable for Hose I.D. (mm)	Order No.
Sealing clamp for AIRDUC® 356 hoses with an inner Ø of <50 mm	
32	216-0032-2010
38	216-0038-2010
40	216-0040-2010
45	216-0045-2010
Sealing clamp for AIRDUC® 345, 355, hoses with an inner Ø of <50 mm	
32	216-0032-2872
38	216-0038-2872
40	216-0040-2872
45	216-0045-2872
Sealing clamp for AIRDUC® 345, 355, 356 hoses with an inner Ø of 50 mm	
50	216-0050-0000
55	216-0055-0000
60	216-0060-0000
65	216-0065-0000
70	216-0070-0000
75	216-0075-0000
80	216-0080-0000
90	216-0090-0000
100	216-0100-0000
102	216-0102-0000
110	216-0110-0000
115	216-0115-0000
120	216-0120-0000
125	216-0125-0000
127	216-0127-0000
130	216-0130-0000
140	216-0140-0000


CLAMP 216

Suitable for Hose I.D.	Order No.
(mm)	
150	216-0150-0000
152	216-0152-0000
160	216-0160-0000
175	216-0175-0000
180	216-0180-0000
200	216-0200-0000
225	216-0225-0000
250	216-0250-0000
275	216-0275-0000
300	216-0300-0000

Accessories



CONNECT 270-271



CONNECT 228