

CLAMP 212 EC



Bridge Clamp with integral grounding (via earth strip) for attaching externally corrugated spiral hoses

Properties

- grounding without exposing spiral and without damaging hose
- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- easily and quickly fitted
- re-usable
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH
- Quality: W2; clamp strip: stainless steel 1.4301 = AISI 304; screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; bridge: stainless steel 1.4301 = AISI 304 (INOX)

Delivery variants

- further diameters available on request

Suitable for Hose I.D. (mm)	Clamping Range (mm)	Band Width (mm)	Order No.
Clamp with earthing wire			
38-45	35-55	9	212-0035-2878
50-55	45-65	9	212-0045-2878
60-65	55-75	9	212-0055-2878
70-75	65-85	9	212-0065-2878
80-85	75-95	9	212-0075-2878
90-95	85-105	9	212-0085-2878
100-105	95-115	9	212-0095-2878
110-115	105-125	9	212-0105-2878
120-127	115-135	9	212-0115-2878
130-135	125-145	9	212-0125-2878
140-145	135-155	9	212-0135-2878
150-155	145-165	9	212-0145-2878
160-165	155-175	9	212-0155-2878
170-175	165-185	9	212-0165-2878
190-195	185-205	9	212-0185-2878
200-205	195-215	9	212-0195-2878
210-215	205-225	12	212-0205-2878
220-225	215-235	12	212-0215-2878
250-255	245-265	12	212-0245-2878
270-275	265-285	12	212-0265-2878
280-285	275-295	12	212-0275-2878
300-305	295-315	12	212-0295-2878
320-325	315-335	12	212-0315-2878
350-355	345-365	12	212-0345-2878
380-385	375-395	12	212-0375-2878
400-405	395-415	12	212-0395-2878
450-455	445-465	12	212-0445-2878
500-505	495-515	12	212-0495-2878

CLAMP 212 EC

Accessories



CONNECT 270-271