

CLAMP 217



Bridge clamp with eyelet for attaching externally corrugated spiral hoses

Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable

- re-usable

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Design

- Quality: W2; Clamp strip: stainless steel 1.4016 = AISI 430; screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; bridge: stainless steel 1.4301 = AISI 304 (INOX); fixing eyelet: galvanised steel

Delivery variants

- further diameters available on request

Suitable for Hose I.D.	Clamping Range	Band Width	Order No.
(mm)	(mm)	(mm)	
70-75	65-85	9	217-0065-0000
90-95	85-105	9	217-0085-0000
100-105	95-115	9	217-0095-0000
110-115	105-125	9	217-0105-0000
120-127	115-135	9	217-0115-0000
130-135	125-145	9	217-0125-0000
140-145	135-155	9	217-0135-0000
160-165	155-175	9	217-0155-0000
170-175	165-185	9	217-0165-0000
180-185	175-195	9	217-0175-0000
200-205	195-215	9	217-0195-0000
210-215	205-225	12	217-0205-0000
220-225	215-235	12	217-0215-0000
250-255	245-265	12	217-0245-0000
270-275	265-285	12	217-0265-0000
280-285	275-295	12	217-0275-0000
300-305	295-315	12	217-0295-0000
320-325	315-355	12	217-0315-0000
350-355	345-365	12	217-0345-0000
380-385	375-395	12	217-0375-0000
400-405	395-415	12	217-0395-0000
450-455	445-465	12	217-0445-0000
500-505	495-515	12	217-0495-0000