



Soft sleeve to slide onto connectors or push into pipes

Application

- industrial vacuum cleaners, vacuum cleaners
- municipal vehicle: sweeper, sweeping machine
- municipal vehicle: lawn mower, slope mower, leaf blower/ leaf collector
- scrubber, floor cleaning machine

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas and liquid tight as pre-fitted version

- gas and liquid tight as pre-fitted version
- highly abrasion resistant
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- version 241 - permanently antistatic wall: electrical and surface resistance approx. $10^9 \Omega$
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40°C to 90°C

- short time to 125°C

Design

- wall: special premium ester-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured
- gas and liquid tight as pre-fitted version

Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	

Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345

38	44	40	85	0,085	38	240-0038-0000
40	44	40	85	0,084	40	240-0040-0000
50	49	41	90	0,089	50	240-0050-0000
60	49	41	90	0,120	60	240-0060-0000
70	52	44	100	0,146	70	240-0070-0000
32	44	40	85	0,070	32	241-0032-8500
75	60	47	107	0,200	75	241-0075-8500
80	60	52	112	0,250	80	241-0080-8500
100	65	57	122	0,310	100	241-0100-8500
125	75	62	137	0,480	125	241-0125-8500
150	85	70	155	0,680	150	241-0150-8500
200	100	80	180	1,100	200	241-0200-8500
250	105	90	195	1,500	250	241-0250-8500
300	115	100	215	2,260	300	241-0300-8500

Threaded; Suitable for Hose 356

38	44	40	85	0,070	38	241-0038-8501
40	44	40	85	0,080	40	241-0040-8501
50	49	41	90	0,080	50	241-0050-8501
60	49	41	90	0,120	60	241-0060-8501
70	52	44	100	0,150	70	241-0070-8501
75	60	47	107	0,200	75	241-0075-8501
80	60	52	112	0,250	80	241-0080-8501
100	65	57	122	0,310	100	241-0100-8501
125	75	62	137	0,480	125	241-0125-8501
150	85	70	155	0,680	150	241-0150-8501

CONNECT 240 + 241 AS



Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
200	100	80	180	1,100	200	241-0200-8501
250	105	90	195	1,500	250	241-0250-8501
300	115	100	215	2,260	300	241-0300-8501

pre-fitted						
38	44	40	85	0,070	38	241-0038-8551
40	44	40	85	0,080	40	241-0040-8551
50	49	41	90	0,080	50	241-0050-8551
60	49	41	90	0,120	60	241-0060-8551
70	52	44	100	0,150	70	241-0070-8551
75	60	47	107	0,200	75	241-0075-8551
80	60	52	112	0,250	80	241-0080-8551
100	65	57	122	0,310	100	241-0100-8551
125	75	62	137	0,480	125	241-0125-8551
150	85	70	155	0,680	150	241-0150-8551
200	100	80	180	1,100	200	241-0200-8551
250	105	90	195	1,500	250	241-0250-8551
300	115	100	215	2,260	300	241-0300-8551