



Soft sleeve to slide onto connectors or push into pipes, foodgrade

Application

- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system
- pelleting machines/ tablet presses
- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas and liquid tight as pre-fitted version

- gas and liquid tight as pre-fitted version
- highly abrasion resistant
- version 241: material food grade according to EU 10/2011, FDA 21 CFR § 177.1680 and CFR § 177.2600
- Food grade wall, complies with: EU-Directive 10/2011 and EC 1935/2004 and the latest EU-Directive 2015/174
- odourless and tasteless
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40°C to 90°C
- short time to 125°C

Design

- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- special colours: full coloured

Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
38	44	40	85	0,085	38	240-0038-0010
40	44	40	85	0,084	40	240-0040-0010
50	49	41	90	0,089	50	240-0050-0010
60	49	41	90	0,120	60	240-0060-0010
70	52	44	100	0,146	70	240-0070-0010
32	44	40	85	0,070	32	241-0032-8600
75	60	47	107	0,200	75	241-0075-8600
80	60	52	112	0,250	80	241-0080-8600
100	65	57	122	0,310	100	241-0100-8600
125	75	62	137	0,480	125	241-0125-8600
150	85	70	155	0,680	150	241-0150-8600
200	100	80	180	1,100	200	241-0200-8600
250	105	90	195	1,500	250	241-0250-8600
300	115	100	215	2,260	300	241-0300-8600
pre-fitted						
32	44	40	85	0,070	32	241-0032-8550
38	44	40	85	0,070	38	241-0038-8550
40	44	40	85	0,080	40	241-0040-8550
50	49	41	90	0,080	50	241-0050-8550
60	49	41	90	0,120	60	241-0060-8550
70	52	44	100	0,150	70	241-0070-8550
75	60	47	107	0,200	75	241-0075-8550
80	60	52	112	0,250	80	241-0080-8550

CONNECT 240 + 241 FOOD



Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
100	65	57	122	0,310	100	241-0100-8550
125	75	62	137	0,480	125	241-0125-8550
150	85	70	155	0,680	150	241-0150-8550
200	100	80	180	1,100	200	241-0200-8550
250	105	90	195	1,500	250	241-0250-8550
300	115	100	215	2,260	300	241-0300-8550

Threaded; Suitable for Hose 356						
38	44	40	85	0,070	38	241-0038-8601
40	44	40	85	0,080	40	241-0040-8601
50	49	41	90	0,080	50	241-0050-8601
60	49	41	90	0,120	60	241-0060-8601
70	52	44	100	0,150	70	241-0070-8601
75	60	47	107	0,200	75	241-0075-8601
80	60	52	112	0,250	80	241-0080-8601
100	65	57	122	0,310	100	241-0100-8601
125	75	62	137	0,480	125	241-0125-8601
150	85	70	155	0,680	150	241-0150-8601
200	100	80	180	1,100	200	241-0200-8601
250	105	90	195	1,500	250	241-0250-8601
300	115	100	215	2,260	300	241-0300-8601