



Threaded adapter

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas and liquid tight as pre-fitted version
- highly abrasion resistant
- good resistance to oil, gasoline and chemicals

- thread reference DIN ISO 228
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C

Design

- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured
- gas and liquid tight as pre-fitted version

Threading depth Hose (mm)	Thread Length (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345					
45	23,8	86	0,150	50	242-0050-8500
45	25,5	87	0,180	55	242-0055-8500
45	26,5	89	0,220	65	242-0065-8500
47	29,8	97	0,280	75	242-0075-8500
51	35,8	108	0,450	100	242-0100-8500
58	40	122	0,800	125	242-0125-8500
68	40	132	1,000	150	242-0150-8500
Threaded; Suitable for Hose 356					
45	23,8	86	0,150	50	242-0050-8501
45	25,5	87	0,180	55	242-0055-8501
45	26,5	89	0,220	65	242-0065-8501
47	29,8	97	0,280	75	242-0075-8501
51	35,8	108	0,450	100	242-0100-8501
58	40	122	0,800	125	242-0125-8501
68	40	132	1,000	150	242-0150-8501
pre-fitted; (please select the hose separately)					
45	23,8	86	0,150	50	242-0050-8551
45	25,5	87	0,180	55	242-0055-8551
45	26,5	89	0,220	65	242-0065-8551
47	29,8	97	0,280	75	242-0075-8551
51	35,8	108	0,450	100	242-0100-8551
58	40	122	0,800	125	242-0125-8551
68	40	132	1,000	150	242-0150-8551