



Flanged pipe according to the popular pipe systems in the ventilation field (for example Jacob-Standard)

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas and liquid tight as pre-fitted version
- highly abrasion resistant
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals

- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 60 °C

Design

- flanged pipe: galvanised sheet metal

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured
- Stainless Steel (INOX)
- gas and liquid tight as pre-fitted version

Suitable for Ø-Pipe System (mm)	Threading depth Hose (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345					
80	46	136	0,380	80	243-0080-8500
100	51	141	0,580	100	243-0100-8500
120	58	148	0,870	120	243-0120-8500
150	68	158	1,100	150	243-0150-8500
200	80	170	1,810	200	243-0200-8500
250	90	180	2,700	250	243-0250-8500
300	100	190	3,340	300	243-0300-8500
Threaded; Suitable for Hose 356					
80	46	136	0,380	80	243-0080-8501
100	51	141	0,580	100	243-0100-8501
120	58	148	0,870	120	243-0120-8501
150	68	158	1,100	150	243-0150-8501
200	80	170	1,810	200	243-0200-8501
250	90	180	2,700	250	243-0250-8501
300	100	190	3,340	300	243-0300-8501
pre-fitted					
80	46	136	0,380	80	243-0080-8551
100	51	141	0,580	100	243-0100-8551
120	58	148	0,870	120	243-0120-8551
150	68	158	1,100	150	243-0150-8551
200	80	170	1,810	200	243-0200-8551
250	90	180	2,700	250	243-0250-8551
300	100	190	3,340	300	243-0300-8551

