



Flanged pipe according to the popular pipe systems in the ventilation field (for example Jacob-Standard), food-grade

Application

- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system
- pelleting machines/ tablet presses

Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas and liquid tight as pre-fitted version

- gas and liquid tight as pre-fitted version
- highly abrasion resistant
- Food grade wall, complies with: EU-Directive 10/2011 and EC 1935/2004 and the latest EU-Directive 2015/174
- odourless and tasteless
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

- -40 °C to 90 °C

Design

- flanged pipe: Stainless Steel (INOX)
- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters and lengths available on request
- special colours: full coloured

Suitable for Ø-Pipe System (mm)	Threading depth Hose (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Threaded; Suitable for Hose 356					
80	46	136	0,380	80	243-0080-8509
100	51	141	0,580	100	243-0100-8509
120	58	148	0,870	120	243-0120-8509
150	68	158	1,100	150	243-0150-8509
200	80	170	1,810	200	243-0200-8509
250	90	180	2,700	250	243-0250-8509
300	100	190	3,340	300	243-0300-8509
pre-fitted					
80	46	136	0,380	80	243-0080-8559
100	51	141	0,580	100	243-0100-8559
120	58	148	0,870	120	243-0120-8559
150	68	158	1,100	150	243-0150-8559
200	80	170	1,810	200	243-0200-8559
250	90	180	2,700	250	243-0250-8559
300	100	190	3,340	300	243-0300-8559
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345					
80	46	136	0,380	80	243-0080-8610
100	51	141	0,580	100	243-0100-8610
120	58	148	0,870	120	243-0120-8610
150	68	158	1,100	150	243-0150-8610
200	80	170	1,810	200	243-0200-8610
250	90	180	2,700	250	243-0250-8610

