



2-part loose flange to fit mating flanges acc. to DIN 2632/2633, hole pattern DIN-EN 1092-1 (PN10, up to 16 bar ø450 up to 10 bar)



Properties

- easily and quickly fitted
- re-usable (threaded version)
- gas and liquid tight as pre-fitted version
- highly abrasion resistant
- microbe and hydrolysis resistant

- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C

Design

- loose flange: polypropylene (PP) coated steel core
- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- special colours: full coloured
- gas and liquid tight as pre-fitted version

Suitable for Ø-Pipe System (mm)	Fixing Holes Ø (mm)	No. + Ø Fixing Holes (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
51,2	125	4x18	66	1,110	50	244-0050-8500
82,5	160	8x18	76	1,740	80	244-0080-8500
100,8	180	8x18	84	2,030	100	244-0100-8500
126,0	210	8x18	100	3,190	125	244-0125-8500
151,0	240	8x22	114	4,320	150	244-0150-8500
207,3	295	8x22	132	6,380	200	244-0200-8500
254,4	350	12x22	145	9,750	250	244-0250-8500
309,7	400	12x22	155	13,040	300	244-0300-8500
Threaded; Suitable for Hose 356						
51,2	125	4x18	66	1,110	50	244-0050-8501
82,5	160	8x18	76	1,740	80	244-0080-8501
100,8	180	8x18	84	2,030	100	244-0100-8501
126,0	210	8x18	100	3,190	125	244-0125-8501
151,0	240	8x22	114	4,320	150	244-0150-8501
207,3	295	8x22	132	6,380	200	244-0200-8501
254,4	350	12x22	145	9,750	250	244-0250-8501
309,7	400	12x22	155	13,040	300	244-0300-8501
pre-fitted; (please select the hose separately)						
51,2	125	4x18	66	1,110	50	244-0050-8551
82,5	160	8x18	76	1,740	80	244-0080-8551
100,8	180	8x18	84	2,030	100	244-0100-8551
126,0	210	8x18	100	3,190	125	244-0125-8551
151,0	240	8x22	114	4,320	150	244-0150-8551
207,3	295	8x22	132	6,380	200	244-0200-8551
254,4	350	12x22	145	9,750	250	244-0250-8551

CONNECT 244



Suitable for Ø-Pipe System (mm)	Fixing Holes Ø (mm)	No. + Ø Fixing Holes (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
309,7	400	12x22	155	13,040	300	244-0300-8551

Threaded; Suitable for Hose 357						
100,8	180	8x18	84	2,030	102	244-0102-8502
126,0	210	8x18	100	3,190	127	244-0127-8502
151,0	240	8x22	114	4,320	152	244-0152-8502