



TRI-Clamp coupling to fit adapter acc. to DIN 32677

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant
- microbe and hydrolysis resistant

- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C

Design

- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters available on request
- special colours: full coloured

Size (mm)	Outer-Ø flange (mm)	Pipe I.D. (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345						
32	50,5	32	60,0	0,060	32	245-0032-8500
38	50,5	38	65,0	0,070	38	245-0038-8500
50	64	50	67,0	0,120	50	245-0050-8500
65	91	66	67,0	0,180	65	245-0065-8500
80	106	81	72,0	0,200	80	245-0080-8500
100	119	100	77,0	0,330	100	245-0100-8500
125	155	125	91,0	0,480	125	245-0125-8500
150	183	150	102,0	0,670	150	245-0150-8500
200	233,5	200	112,5	0,960	200	245-0200-8500
Threaded; Suitable for Hose 356						
32	50,5	32	60,0	0,060	32	245-0032-8501
38	50,5	38	65,0	0,070	38	245-0038-8501
50	64	50	67,0	0,120	50	245-0050-8501
65	91	66	67,0	0,180	65	245-0065-8501
80	106	81	72,0	0,200	80	245-0080-8501
100	119	100	77,0	0,330	100	245-0100-8501
125	155	125	91,0	0,480	125	245-0125-8501
150	183	150	102,0	0,670	150	245-0150-8501
200	233,5	200	112,5	0,960	200	245-0200-8501
pre-fitted; (please select the hose separately)						
32	50,5	32	60,0	0,060	32	245-0032-8554
38	50,5	38	65,0	0,070	38	245-0038-8554
50	64	50	67,0	0,120	50	245-0050-8554
65	91	66	67,0	0,180	65	245-0065-8554
80	106	81	72,0	0,200	80	245-0080-8554
100	119	100	77,0	0,330	100	245-0100-8554
125	155	125	91,0	0,480	125	245-0125-8554
150	183	150	102,0	0,670	150	245-0150-8554

CONNECT 245



Size	Outer-Ø flange	Pipe I.D.	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
200	233,5	200	112,5	0,960	200	245-0200-8554

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/