



Spiral hose connector for connecting, lengthening or repairing spiral hoses

Application

- industrial vacuum cleaners, vacuum cleaners

Properties

- easily and quickly fitted
- re-usable (threaded version)
- highly abrasion resistant
- microbe and hydrolysis resistant

- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- permanently antistatic wall: electrical and surface resistance approx. $10^9 \Omega$
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C

- short time to 125 °C

Design

- wall: special premium ether-polyurethane (Pre-PUR[®])

Delivery variants

- further diameters available on request
- special colours: full coloured

Size (mm)	Threading depth Hose (mm)	Total Length (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Threaded; Suitable for Hose 350, 351, 355, 533, 341, 345					
25	32	71	0,120	25	246-0025-8500
32	32	71	0,150	32	246-0032-8500
38	37	83	0,170	38	246-0038-8500
40	37	83	0,160	40	246-0040-8500
50	42	95	0,250	50	246-0050-8500
60	47	105	0,300	60	246-0060-8500
70	47	105	0,330	70	246-0070-8500
80	52	117	0,400	80	246-0080-8500
100	57	127	0,650	100	246-0100-8500
Threaded; Suitable for Hose 356					
32	32	71	0,150	32	246-0032-8501
38	37	83	0,170	38	246-0038-8501
40	37	83	0,160	40	246-0040-8501
50	42	95	0,250	50	246-0050-8501
60	47	105	0,300	60	246-0060-8501
70	47	105	0,330	70	246-0070-8501
80	52	117	0,400	80	246-0080-8501
100	57	127	0,650	100	246-0100-8501