


CONNECT 270-271



Metal hose connector / reducer

Properties

- easily and quickly fitted
- re-usable (threaded version)
- conforms to RoHS guideline

- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- 200 °C

Design

- galvanised sheet metal

Delivery variants

- further diameters available on request
- Stainless Steel (INOX)

Suitable for Hose Ø-D1 (mm)	Suitable for Hose Ø-D2 (mm)	Adapter length L1 (mm)	Adapter length L2 (mm)	Total Length (mm)	Wall Thickness (mm)	Weight (kg/pcs)	Order No.
Hose connector							
50	50	40	40	L3: 90	0.60	0,200	270-0050-0000
60	60	40	40	L3: 90	0.60	0,200	270-0060-0000
70	70	40	40	L3: 90	0.60	0,200	270-0070-0000
75	75	40	40	L3: 90	0.60	0,200	270-0075-0000
80	80	40	40	L3: 90	0.60	0,200	270-0080-0000
90	90	40	40	L3: 90	0.60	0,200	270-0090-0000
100	100	40	40	L3: 90	0.60	0,200	270-0100-0000
110	110	40	40	L3: 90	0.60	0,300	270-0110-0000
120	120	40	40	L3: 90	0.60	0,300	270-0120-0000
125	125	40	40	L3: 90	0.60	0,300	270-0125-0000
130	130	40	40	L3: 90	0.60	0,300	270-0130-0000
140	140	40	40	L3: 90	0.60	0,400	270-0140-0000
150	150	40	40	L3: 90	0.60	0,500	270-0150-0000
160	160	40	40	L3: 90	0.60	0,500	270-0160-0000
170	170	40	40	L3: 90	0.60	0,500	270-0170-0000
175	175	40	40	L3: 90	0.60	0,600	270-0175-0000
180	180	40	40	L3: 90	0.60	0,600	270-0180-0000
200	200	40	40	L3: 90	0.60	0,600	270-0200-0000
215	215	40	40	L3: 90	0.60	0,700	270-0215-0000
225	225	40	40	L3: 90	0.60	0,700	270-0225-0000
250	250	60	60	L3: 130	0.60	0,800	270-0250-0000
275	275	60	60	L3: 130	0.60	0,900	270-0275-0000
300	300	60	60	L3: 130	0.70	1,000	270-0300-0000
315	315	60	60	L3: 130	0.70	1,100	270-0315-0000
325	325	60	60	L3: 130	0.70	1,200	270-0325-0000
350	350	60	60	L3: 130	0.70	1,300	270-0350-0000
375	375	80	80	L3: 170	0.70	1,500	270-0375-0000
400	400	80	80	L3: 170	0.70	1,600	270-0400-0000
450	450	80	80	L3: 170	0.70	2,100	270-0450-0000
500	500	80	80	L3: 170	0.70	2,300	270-0500-0000

CONNECT 270-271

Suitable for Hose Ø-D1 (mm)	Suitable for Hose Ø-D2 (mm)	Adapter length L1 (mm)	Adapter length L2 (mm)	Total Length (mm)	Wall Thickness (mm)	Weight (kg/pcs)	Order No.
Hose reduction							
75	50	40	40	L3: 135	0.60	0,200	271-0075-0000
80	70	40	40	L3: 125	0.60	0,200	271-0080-0000
80	50	40	40	L3: 135	0.60	0,200	271-0080-2655
100	80	40	40	L3: 140	0.60	0,200	271-0100-0000
100	70	40	40	L3: 150	0.60	0,200	271-0100-2660
125	100	40	40	L3: 145	0.60	0,300	271-0125-0000
125	80	40	40	L3: 175	0.60	0,300	271-0125-2665
150	100	40	40	L3: 175	0.60	0,300	271-0150-0000
150	80	40	40	L3: 205	0.60	0,400	271-0150-2670
150	125	40	40	L3: 145	0.60	0,300	271-0150-2671
200	150	40	40	L3: 175	0.60	0,500	271-0200-0000
200	100	40	40	L3: 245	0.60	0,600	271-0200-2675
200	125	40	40	L3: 215	0.60	0,600	271-0200-2676
250	200	60	40	L3: 200	0.60	0,800	271-0250-0000
250	125	60	40	L3: 300	0.60	1,000	271-0250-2680
250	150	60	40	L3: 270	0.60	0,900	271-0250-2681
300	200	60	40	L3: 265	0.70	1,200	271-0300-0000
300	150	60	40	L3: 335	0.70	1,300	271-0300-2685
300	250	60	40	L3: 195	0.70	1,300	271-0300-2687

Accessories



CLAMP 212



CLAMP 211



CLAMP 217



CONNECT 228