

CONNECT STORZ DIN ALU 251



Storz suction coupling

Application

- construction industry: lowering groundwater
- wood pellet heating system: conveying of wood pellets

- wood pellet heating system: conveying of wood pellets

Properties

- DIN design - forged aluminium (52-C = DIN 14321 / 75-B = DIN 14322 / 110-A = DIN 14323)

- Not to be used for explosive fluids group 1 and not according to pressure equipment directive

- REACH according to --> Technology / Technical Information / REACH

Size (mm)	Lug Spacing (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
with corrugated nozzle for band clamp fitting; suitable to CONNECT 229 CLAMP ASSEMBLY				
52-C	66	0,35	50	251-0050-8012
75-B	89	0,66	75	251-0075-8012
110-A	133	1,84	100	251-0100-8012
with smooth nozzle and locking ring for clamp shell band fitting; suitable to CONNECT 231 SAFETY CLAMP ASSEMBLY				
52-C	66	0,35	50	251-0050-8022
75-B	89	0,66	75	251-0075-8022
110-A	133	1,84	100	251-0100-8022
replacement seal NBR back				
52-C	66	0,02	-	251-0052-8068
75-B	89	0,03	-	251-0075-8068
110-A	133	0,05	-	251-0110-8068

Accessories



CLAMP 211