



Vacuum cleaner hose, antistatic $<10^{11}$ Ohm

Application

- flexible hose/ ducting for gases and for dust, powder, fibres
- industrial vacuum cleaners, vacuum cleaners
- explosion hazard area
- swimming pool cleaning
- scrubber, floor cleaning machine

Properties

- light weight
- highly flexible

- highly flexible
- crush resistant
- floatable
- good resistance to alkalis and acids
- surface resistance $<10^{11}$
- in accordance with ATEX 2014/34/EU (1999/92/EC) and German TRGS 727: aspiration of combustible dusts (Zone 22 inside), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in Zone 0 (gases)
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

Design

- EVA design
- self-supporting profile design
- open profile geometry
- wall: EVA

Delivery variants

- further diameters and lengths available on request
- black (standard)

I.D.	outer Ø	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(mm)	(kg/m)	(m)	(m)	
- / 20	26.80	0,500	42.00	0.13	-	30	373-0020-1002
1 / 25	32.20	0,500	54.00	0.15	30	-	373-0025-1002
- / 30	38.00	0,500	62.00	0.20	-	30	373-0030-1002
1,25 / 32	40.40	0,500	66.00	0.24	30	-	373-0032-1002
1,36 / 35	43.80	0,500	71.00	0.26	30	-	373-0035-1002
1,5 / 38	47.20	0,500	74.00	0.31	30	-	373-0038-1002
- / 40	49.40	0,500	80.00	0.32	30	-	373-0040-1002
1,75 / 44-45	55.00	0,500	89.00	0.37	30	-	373-0045-1002
2 / 50-51	60.40	0,500	97.00	0.44	30	-	373-0050-1002
2,36 / 60	72.00	0,500	113.00	0.67	30	-	373-0060-1002

Accessories



CONNECT 227



CONNECT 228



CLAMP 208