

PVC air conditioning hose, insulated, flame resistant, black

Application

- flexible hose/ ducting for gases
- air conditioning
- thermal and acoustic insulation

Properties

- fabric reinforced
- highly flexible + compressible 6:1

- insulating
- flame-retardant according to: class 1 (Italy)
- conforms to RoHS guideline

Temperature Range

- 0°C to 75°C

Design

- special thermal insulation layer

- polyester insulation thickness 25 mm and density 17 Kg/m³
- Pressure max. 200 mm H₂O
- Air speed max. 20 m/s
- bending radius 0,6 x ID

Delivery variants


- further diameters and lengths available on request
- black (standard)

I.D.	outer Ø	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	(m)	
3 / 75-76	126.60	0.00	0.00	-	5 6 10	368-0076-3503
- / 82	132.60	0.00	0.00	10	5 6	368-0082-3503
3,5 / 89-90	140.60	0.00	0.00	-	5 6 10	368-0090-3503
4 / 100-102	152.60	0.00	0.00	10	5 6	368-0102-3503
- / 110	160.60	0.00	0.00	-	5 6 10	368-0110-3503
4,72 / 120	171.60	0.00	0.00	-	5 6 10	368-0120-3503
5 / 125-127	177.60	0.00	0.00	10	5 6	368-0127-3503
5,5 / 140	190.60	0.00	0.00	-	5 6 10	368-0140-3503
6 / 150-152	202.60	0.00	0.00	10	5 6	368-0152-3503
6,3 / 160	210.60	0.00	0.00	10	5 6	368-0160-3503
7 / 178-180	230.60	0.00	0.00	10	5 6	368-0180-3503
8 / 200-203	253.60	0.00	0.00	10	5 6	368-0203-3503
9 / 228-229	278.60	0.00	0.00	-	5 6 10	368-0228-3503
10 / 254	304.60	0.00	0.00	10	5 6	368-0254-3503
11 / 280	330.60	0.00	0.00	-	5 6 10	368-0280-3503
12 / 305	355.60	0.00	0.00	10	5 6	368-0305-3503
- / 315	365.60	0.00	0.00	10	5 6	368-0315-3503
14 / 356	406.60	0.00	0.00	10	5 6	368-0356-3503
16 / 405-406	456.60	0.00	0.00	10	5 6	368-0406-3503
18 / 457	507.60	0.00	0.00	10	5 6	368-0457-3503
20 / 508	558.60	0.00	0.00	10	5 6	368-0508-3503
22 / 560	610.60	0.00	0.00	-	5 6 10	368-0560-3503
24 / 610	660.60	0.00	0.00	10	5 6	368-0610-3503

Accessories



CONNECT 228



CLAMP 210 BRIDGE CLAMP



CONNECT 270-271



CLAMP 208