

Aluminium/Polyester air conditioning hose, insulated, sound-absorbing, flame resistant (M1)

### Application

- flexible hose/ ducting for gases
- air conditioning
- thermal and acoustic insulation

### Properties

- insulating
- highly flexible + compressible 10:1

- highly flexible + compressible 10:1
- flame-retardant according to: C.S.T.B. class M1 (France)
- conforms to RoHS guideline

### Temperature Range

- 30 °C bis +140 °C

### Design

- special thermal insulation layer

- polyester insulation thickness 25 mm and density 17 Kg/m<sup>3</sup>
- Pressure max. 300 mm H<sub>2</sub>O
- Air speed max. 30 m/s

### Delivery variants

- further diameters and lengths available on request
- silver

I.D.	outer Ø	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	(m)	
3 / 75-76	77.60	0.00	0.00	10	5 6	368-0076-3504
- / 82	84.96	0.00	0.00	10	5 6	368-0082-3504
4 / 100-102	105.00	0.00	0.00	10	5 6	368-0102-3504
4,72 / 120	124.00	0.00	0.00	-	5 6 10	368-0120-3504
5 / 125-127	130.00	0.00	0.00	10	5 6	368-0127-3504
6 / 150-152	155.36	0.00	0.00	10	5 6	368-0152-3504
6,3 / 160	163.40	0.00	0.00	10	5 6	368-0160-3504
7 / 178-180	183.40	0.00	0.00	10	5 6	368-0180-3504
8 / 200-203	206.40	0.00	0.00	10	5 6	368-0203-3504
9 / 228-229	231.40	0.00	0.00	-	5 6 10	368-0228-3504
10 / 254	257.40	0.00	0.00	10	5 6	368-0254-3504
11 / 280	283.40	0.00	0.00	-	5 6 10	368-0280-3504
12 / 305	305.40	0.00	0.00	10	5 6	368-0305-3504
- / 315	318.40	0.00	0.00	10	5 6	368-0315-3504
14 / 356	359.40	0.00	0.00	10	5 6	368-0356-3504
16 / 405-406	409.40	0.00	0.00	10	5 6	368-0406-3504
18 / 457	461.16	0.00	0.00	10	5 6	368-0457-3504
20 / 508	512.20	0.00	0.00	10	5 6	368-0508-3504
22 / 560	564.20	0.00	0.00	-	5 6 10	368-0560-3504
24 / 610	614.20	0.00	0.00	10	5 6	368-0610-3504

## Accessories




CLAMP 208



CONNECT 228



CONNECT 270-271



CLAMP 210 BRIDGE CLAMP