

Aluminium/Polyester air conditioning hose, flame resistant (M0)

Application

- flexible hose/ ducting for gases
- air conditioning in marine applications

Properties

- super-light weight
- highly flexible + compressible 10:1

- flame-retardant according to: C.S.T.B. class M0 (France)
- flame-retardant according to: non-combustible according to BUREAU VERITAS standards (France)
- conforms to RoHS guideline

Temperature Range

- 30°C bis +250°C

Design


- PROTAPE® tape hose
- Pressure max. 300 mm H2O
- Air speed max. 30 m/s

Delivery variants

- further diameters and lengths available on request
- silver

I.D.	outer Ø	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	(m)	
3 / 75-76	77.60	0.00	0.00	10	5 6	369-0076-3507
- / 82	84.96	0.00	0.00	10	5 6	369-0082-3507
4 / 100-102	105.00	0.00	0.00	10	5 6	369-0102-3507
4,72 / 120	124.00	0.00	0.00	-	5 6 10	369-0120-3507
5 / 125-127	130.00	0.00	0.00	10	5 6	369-0127-3507
6 / 150-152	155.36	0.00	0.00	10	5 6	369-0152-3507
6,3 / 160	163.40	0.00	0.00	10	5 6	369-0160-3507
7 / 178-180	183.40	0.00	0.00	10	5 6	369-0180-3507
8 / 200-203	206.40	0.00	0.00	10	5 6	369-0203-3507
9 / 228-229	231.40	0.00	0.00	-	5 6 10	369-0228-3507
10 / 254	257.40	0.00	0.00	10	5 6	369-0254-3507
11 / 280	283.40	0.00	0.00	-	5 6 10	369-0280-3507
12 / 305	305.40	0.00	0.00	10	5 6	369-0305-3507
- / 315	318.40	0.00	0.00	10	5 6	369-0153-3507
14 / 356	359.40	0.00	0.00	10	5 6	369-0356-3507
16 / 405-406	409.40	0.00	0.00	10	5 6	369-0406-3507
18 / 457	461.16	0.00	0.00	10	5 6	369-0457-3507
20 / 508	512.20	0.00	0.00	10	5 6	369-0508-3507
22 / 560	564.20	0.00	0.00	-	5 6 10	369-0560-3507
24 / 610	614.20	0.00	0.00	10	5 6	369-0610-3507

Accessories



CONNECT 228



CLAMP 208



CONNECT 270-271



CLAMP 210 BRIDGE CLAMP