



Aluminium air conditioning hose, flame retardant (M0), self-locking

Application

- flexible hose/ ducting for gases
- air conditioning in marine applications
- kitchen hood, fume hood, exhaust air duct

Properties

- highly flexible + compressible 3:1

- highly flexible + compressible 3:1
- retaining any adjusted position
- conforms to RoHS guideline

Temperature Range

- 300°C

Design

- Metal hose
- Pressure max. 300 mm H2O

Delivery variants

- silver
- further diameters and lengths available on request

I.D.	outer Ø	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	(m)	
3 / 75-76	85.00	38.00	0.00	3	5	377-0075-1000
- / 80	90.00	40.00	0.00	3	5	377-0080-1000
3,5 / 89-90	100.00	45.00	0.00	3	5	377-0090-1000
4 / 100-102	110.00	50.00	0.00	3	5	377-0100-1000
- / 110	120.00	55.00	0.00	3	5	377-0110-1000
4,72 / 120	130.00	60.00	0.00	3	5	377-0120-1000
5 / 125-127	135.00	63.00	0.00	3	5	377-0125-1000
- / 130	140.00	65.00	0.00	-	3 5	377-0130-1000
5,5 / 140	150.00	70.00	0.00	3	5	377-0140-1000
6 / 150-152	160.00	75.00	0.00	3	5	377-0150-1000
6,3 / 160	170.00	80.00	0.00	3	5	377-0160-1000
7 / 178-180	190.00	90.00	0.00	3	5	377-0180-1000
8 / 200-203	210.00	100.00	0.00	3	5	377-0200-1000
- / 250	260.00	125.00	0.00	3	5	377-0250-1000
11 / 280	290.00	140.00	0.00	3	5	377-0280-1000
- / 300	310.00	150.00	0.00	3	5	377-0300-1000
- / 315	325.00	158.00	0.00	3	-	377-0315-1000
- / 350	360.00	175.00	0.00	3	-	377-0350-1000
- / 400	410.00	200.00	0.00	3	-	377-0400-1000
- / 450	460.00	225.00	0.00	3	-	377-0450-1000

Accessories

METAL HOSE ALU 377 - ALUFLEX



CONNECT 270-271



CLAMP 208