



PVC hose

### Application

- flexible hose/ ducting for liquids and for gases
- hose/ tubing pump
- industrial washing machine: washing water hose
- compressed air hose, cooling water hose, water hose
- heating hose: interior hose for media transfer

### Properties

- highly flexible

- crush resistant
- good resistance to alkalis and acids
- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- -20°C to 60°C

### Design

- NORFLEX® design
- wall interior and exterior smooth
- wall: soft PVC

### Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colours: full coloured
- customer-specific branding

| I.D.       | outer Ø | Wall Thickness | Weight | Dimensions in Stock | Order No.     |
|------------|---------|----------------|--------|---------------------|---------------|
| (in / mm)  | (mm)    | mm             | (kg/m) | (m)                 |               |
| - / 2      | 4.00    | 1.00           | 0.01   | 100                 | 400-9020-0000 |
| 1/8 / 3    | 5.00    | 1.00           | 0.02   | 100                 | 400-9030-0000 |
| - / 4      | 6.00    | 1.00           | 0.02   | 100                 | 400-9040-0000 |
| - / 4      | 7.00    | 1.50           | 0.03   | 100                 | 400-9040-2182 |
| - / 5      | 8.00    | 1.50           | 0.04   | 100                 | 400-9050-0000 |
| 1/4 / 6    | 9.00    | 1.50           | 0.05   | 100                 | 400-9060-0000 |
| 1/4 / 6    | 10.00   | 2.00           | 0.07   | 100                 | 400-9060-2184 |
| - / 7      | 10.00   | 1.50           | 0.05   | 100                 | 400-9070-0000 |
| 5/16 / 8   | 12.00   | 2.00           | 0.08   | 50                  | 400-9080-0000 |
| - / 9      | 13.00   | 2.00           | 0.09   | 50                  | 400-9090-0000 |
| 3/8 / 10   | 14.00   | 2.00           | 0.10   | 50                  | 400-9100-0000 |
| - / 12     | 17.00   | 2.50           | 0.15   | 50                  | 400-9120-0000 |
| - / 14     | 19.00   | 2.50           | 0.17   | 50                  | 400-9140-0000 |
| - / 15     | 20.00   | 2.50           | 0.18   | 50                  | 400-9150-0000 |
| 5/8 / 16   | 22.00   | 3.00           | 0.23   | 50                  | 400-9160-0000 |
| - / 18     | 24.00   | 3.00           | 0.26   | 50                  | 400-9180-0000 |
| - / 20     | 24.00   | 2.00           | 0.18   | 50                  | 400-9200-0000 |
| - / 20     | 26.00   | 3.00           | 0.28   | 50                  | 400-9200-2175 |
| 7/8 / 22   | 28.00   | 3.00           | 0.31   | 50                  | 400-9220-0000 |
| 1 / 25     | 31.00   | 3.00           | 0.34   | 25                  | 400-9250-0000 |
| 1 1/8 / 30 | 37.00   | 3.50           | 0.48   | 25                  | 400-9300-0000 |
| 1 1/4 / 32 | 40.00   | 4.00           | 0.59   | 25                  | 400-9320-0000 |
| 1 1/2 / 38 | 48.00   | 5.00           | 0.88   | 25                  | 400-9380-0000 |
| - / 40     | 48.00   | 4.00           | 0.72   | 25                  | 400-9400-0000 |
| - / 40     | 50.00   | 5.00           | 0.92   | 25                  | 400-9400-2187 |
| - / 50     | 60.00   | 5.00           | 1.12   | 25                  | 400-9500-0000 |

---

## Accessories



CLAMP 208