



TPE hose/ tubing

Application

- flexible hose/ ducting for liquids and for gases
- hose/ tubing pump
- heating hose: interior hose for media transfer
- compressed air hose, cooling water hose, water hose

Properties

- highly flexible
- crush resistant

- crush resistant
- very good heat resistance
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40°C to 125°C
- short time to 150°C

Design

- NORFLEX® design
- wall interior and exterior smooth
- wall: thermoplastic rubber (TPE)

Delivery variants

- further diameters and lengths available on request
- customer-specific branding

I.D.	outer Ø	Wall Thickness	Pressure	Bending Radius	Weight	Production Lengths	Order No.
(in / mm)	(mm)	mm	(bar)	(mm)	(kg/m)	(m)	
cream							
1/4 / 6	10.00	2.00	1,00	30.00	0.06	50	405-9060-0000
1/2 / 12,7	19.10	3.20	0,75	62.00	0.17	50	405-9127-0000
5/8 / 15,9	25.50	4.80	0,60	80.00	0.20	50	405-9159-0000
3/4 / 19	28.60	4.80	0,50	100.00	0.28	50	405-9190-0000
black							
3/8 / 9,5	15.80	3.15	1,20	45.00	0.13	50	405-9095-5300
3/8 / 9,5	13.50	2.00	1,00	40.00	0.08	50	405-9095-5301

Accessories



CLAMP 208