



Silicone hose/ tubing

**Application**

- flexible hose/ ducting for liquids and for gases
- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- hose/ tubing pump
- heating hose: interior hose for media transfer

**Properties**

- highly flexible

- highly flexible
- crush resistant
- food grade wall, complies with: FDA 21 CFR 177.2600, German guideline XV BfR
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

**Temperature Range**

- -60°C to 180°C

- NORFLEX® design
- wall interior and exterior smooth
- wall: silicone 60 ± 5 Shore A

**Delivery variants**

- further diameters and lengths available on request
- transparent (standard)

I.D.	outer Ø	Wall Thickness	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	mm	(kg/m)	(m)	
- / 2	4.00	1.00	0.01	50	408-9020-0000
- / 2	6.00	2.00	0.03	50	408-9020-2163
1/8 / 3	5.00	1.00	0.02	50	408-9030-0000
1/8 / 3	7.00	2.00	0.04	50	408-9030-2163
1/8 / 3	6.00	1.50	0.03	50	408-9030-2182
- / 4	6.00	1.00	0.02	50	408-9040-0000
- / 4	8.00	2.00	0.05	50	408-9040-2163
- / 4	7.00	1.50	0.03	50	408-9040-2182
- / 5	7.00	1.00	0.02	50	408-9050-0000
- / 5	8.00	1.50	0.04	50	408-9050-2182
1/4 / 6	9.00	1.50	0.04	50	408-9060-0000
1/4 / 6	10.00	2.00	0.06	50	408-9060-2163
- / 7	10.00	1.50	0.05	50	408-9070-0000
5/16 / 8	10.00	1.00	0.03	50	408-9080-0000
5/16 / 8	12.00	2.00	0.07	50	408-9080-2163
5/16 / 8	14.00	3.00	0.11	50	408-9080-2175
- / 9	13.00	2.00	0.08	50	408-9090-0000
3/8 / 10	14.00	2.00	0.09	50	408-9100-0000
3/8 / 10	15.00	2.50	0.11	50	408-9100-2174
- / 12	16.00	2.00	0.10	50	408-9120-0000
- / 12	18.00	3.00	0.17	25	408-9120-2175
- / 15	21.00	3.00	0.20	25	408-9150-0000
5/8 / 16	22.00	3.00	0.21	25	408-9160-0000
- / 20	26.00	3.00	0.27	25	408-9200-0000
1 / 25	31.00	3.00	0.31	20	408-9250-0000

Accessories



CLAMP 208