



Silicone hose/ tubing, fabric reinforced pressure hose

### Application

- flexible hose/ ducting for liquids and for gases
- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- fabric reinforced hose/ braided hose
- heating hose: interior hose for media transfer

### Properties

- fabric reinforced
- highly flexible

- highly flexible
- crush resistant
- food grade wall, complies with: FDA 21 CFR 177.2600, German guideline XV BfR
- platinum-cured odourless and tasteless
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- 60°C to 180°C

### Design

- NORFLEX® design
- fabric reinforced wall
- smooth interior and exterior
- wall: silicone 70 ± 5 Shore A

### Delivery variants

- further diameters and lengths available on request

I.D. (in / mm)	outer Ø (mm)	Wall Thickness mm	Pressure (bar)	Bending Radius (mm)	Weight (kg/m)	Dimensions in Stock (m)	Order No.
<b>peroxide cured Colour red</b>							
1/8 / 3	8.00	2.50	16,000	24.00	0.06	25	448-9030-0000
- / 4	9.00	2.50	15,000	33.00	0.07	25	448-9040-0000
- / 5	11.00	3.00	13,000	33.00	0.09	25	448-9050-0000
1/4 / 6	12.00	3.00	12,000	37.00	0.10	25	448-9060-0000
5/16 / 8	14.40	3.20	10,000	41.00	0.15	25	448-9080-0000
3/8 / 10	17.00	3.50	9,000	45.00	0.18	25	448-9100-0000
1/2 / 13	21.00	3.50	8,000	64.00	0.22	25	448-9130-0000
5/8 / 16	25.00	4.50	7,000	72.00	0.30	25	448-9160-0000
3/4 / 19	28.00	4.50	6,000	81.00	0.95	25	448-9190-0000
<b>platinum cured Colour blue</b>							
1/8 / 3	8.00	2.50	16,000	24.00	0.06	25	448-9030-3130
- / 4	9.00	2.50	15,000	33.00	0.07	25	448-9040-3130
- / 5	11.00	3.00	13,000	33.00	0.09	25	448-9050-3130
1/4 / 6	12.00	3.00	12,000	37.00	0.10	25	448-9060-3130
5/16 / 8	14.40	3.20	10,000	41.00	0.15	25	448-9080-3130
3/8 / 10	17.00	3.50	9,000	45.00	0.18	25	448-9100-3130
1/2 / 13	21.00	3.50	8,000	64.00	0.22	25	448-9130-3130
5/8 / 16	25.00	4.50	7,000	72.00	0.30	25	448-9160-3130
3/4 / 19	28.00	4.50	6,000	81.00	0.95	25	448-9190-3130

Accessories



CLAMP 208