



Crush resistant exhaust gas hose

Application

- flexible hose/ ducting for hot gases
- vehicle gas exhaust system, car gas extraction: hose reel, slotted floor channel, underfloor extraction system
- engine test bench, exhaust gas measurement

Properties

- fabric reinforced
- highly flexible + compressible
- protected, flow-optimizing exterior folds
- vibration resistant

- crush resistant
- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- exhaust gas temperatures to 200°C *
- * when correctly applied with exhaust gas funnels and sufficient fresh air supply (50% approx.).

Design

- patented PROTAPE® tape hose

- special plastic-profile supporting spiral
- fabric-reinforced tape
- wall: EPDM/ PP coated fabric
- wall thickness 0,4 mm approx.

Delivery variants

- further diameters and lengths available on request
- black (standard)
- special colours: coloured spiral
- customer-specific branding

I.D.	outer Ø	Vacuum	Bending Radius	Weight	Dimensions in Stock	Order No.
(in / mm)	(mm)	(bar)	(mm)	(kg/m)	(m)	
2 / 50-51	68.00	0,400	57.00	0.38	10 15	326-0051-0000
2,5 / 63-65	80.00	0,280	70.00	0.48	10 15	326-0063-0000
3 / 75-76	93.00	0,170	73.00	0.54	5 6 7,5 10 12,5 15	326-0076-0000
4 / 100-102	119.00	0,050	71.00	0.71	5 6 7,5 10 12,5 15	326-0102-0000
5 / 125-127	144.00	0,035	89.00	0.87	5 6 7,5 10 12,5 15	326-0127-0000
6 / 150-152	169.00	0,030	106.00	1040.00	5 6 7,5 10 12,5 15	326-0152-0000
8 / 200-203	220.00	0,010	143.00	1.37	5 6 7,5 10	326-0203-0000

Accessories



CONNECT 270-271



CONNECT 228



CLAMP 217



CLAMP 213



CLAMP 212