



PVC air conditioning hose, flame resistant, grey

Application

- flexible hose/ ducting for gases
- ventilation, air conditioning, heating system

Properties

- fabric reinforced
- super-light weight
- highly flexible + compressible 10:1

- approved to FMVSS 302 (flame-retardant)
- conforms to RoHS guideline

Temperature Range

- 10°C to 80°C

Design

- PROTAPE® tape hose
- spring steel wire integrated in wall

- wall: PVC coated fabric
- wall thickness 0.2 mm approx.
- Pressure max. 200 mm H₂O
- bending radius 0,6 x ID

Delivery variants

- further diameters and lengths available on request
- grey (standard)

I.D.	outer Ø	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	(m)	
3 / 75-76	77.60	0.00	0.00	-	5 6 10	371-0076-3500
- / 82	84.96	0.00	0.00	10	5 6	371-0082-3500
3,5 / 89-90	93.00	0.00	0.00	-	5 6 10	371-0090-3500
4 / 100-102	105.00	0.00	0.00	10	5 6	371-0102-3500
- / 110	113.00	0.00	0.00	-	5 6 10	371-0110-3500
4,72 / 120	123.00	0.00	0.00	-	5 6 10	371-0120-3500
5 / 125-127	130.00	0.00	0.00	10	5 6	371-0127-3500
5,5 / 140	143.00	0.00	0.00	-	5 6 10	371-0140-3500
6 / 150-152	155.36	0.00	0.00	10	5 6	371-0152-3500
6,3 / 160	163.40	0.00	0.00	10	5 6	371-0160-3500
7 / 178-180	183.40	0.00	0.00	10	5 6	371-0180-3500
8 / 200-203	206.40	0.00	0.00	10	5 6	371-0203-3500
9 / 228-229	231.40	0.00	0.00	-	5 6 10	371-0228-3500
10 / 254	257.40	0.00	0.00	10	5 6	371-0254-3500
11 / 280	283.40	0.00	0.00	-	5 6 10	371-0280-3500
12 / 305	305.40	0.00	0.00	10	5 6	371-0305-3500
- / 315	318.40	0.00	0.00	10	5 6	371-0315-3500
14 / 356	359.40	0.00	0.00	10	5 6	371-0356-3500
16 / 405-406	409.40	0.00	0.00	10	5 6	371-0406-3500
18 / 457	461.16	0.00	0.00	10	5 6	371-0457-3500
20 / 508	512.20	0.00	0.00	10	5 6	371-0508-3500
22 / 560	564.20	0.00	0.00	-	5 6 10	371-0560-3500
24 / 610	614.20	0.00	0.00	10	5 6	371-0610-3500

Accessories



CONNECT 228



CLAMP 208



CONNECT 270-271



CLAMP 210 BRIDGE CLAMP