



PVC air conditioning hose, flame resistant, black

Application

- flexible hose/ ducting for gases
- ventilation, air conditioning, heating system

Properties

- fabric reinforced
- super-light weight
- highly flexible + compressible 6:1

- highly flexible + compressible 6:1
- flame-retardant according to: class 1 (Italy)
- conforms to RoHS guideline

Temperature Range

- 0°C to 75°C

Design

- PROTAPE® tape hose

- Pressure max. 200 mm H2O
- Air speed max. 20 m/s
- bending radius 0,6 x ID

Delivery variants

- further diameters and lengths available on request
- black (standard)

I.D.	outer Ø	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	(m)	
3 / 75-76	77.60	0.00	0.00	-	5 6 10	371-0076-3503
- / 82	84.96	0.00	0.00	10	5 6	371-0082-3503
3,5 / 89-90	93.00	0.00	0.00	-	5 6 10	371-0090-3503
4 / 100-102	105.00	0.00	0.00	10	5 6	371-0102-3503
- / 110	113.00	0.00	0.00	-	5 6 10	371-0110-3503
4,72 / 120	123.00	0.00	0.00	-	5 6 10	371-0120-3503
5 / 125-127	130.00	0.00	0.00	10	5 6	371-0127-3503
5,5 / 140	143.00	0.00	0.00	-	5 6 10	371-0140-3503
6 / 150-152	155.36	0.00	0.00	10	5 6	371-0152-3503
6,3 / 160	163.40	0.00	0.00	10	5 6	371-0160-3503
7 / 178-180	183.40	0.00	0.00	10	5 6	371-0180-3503
8 / 200-203	206.40	0.00	0.00	10	5 6	371-0203-3503
9 / 228-229	231.40	0.00	0.00	-	5 6 10	371-0228-3503
10 / 254	257.40	0.00	0.00	10	5 6	371-0254-3503
11 / 280	283.40	0.00	0.00	-	5 6 10	371-0280-3503
12 / 305	305.40	0.00	0.00	10	5 6	371-0305-3503
- / 315	318.40	0.00	0.00	10	5 6	371-0315-3503
14 / 356	359.40	0.00	0.00	10	5 6	371-0356-3503
16 / 405-406	409.40	0.00	0.00	10	5 6	371-0406-3503
18 / 457	461.16	0.00	0.00	10	5 6	371-0457-3503
20 / 508	512.20	0.00	0.00	10	5 6	371-0508-3503
22 / 560	564.20	0.00	0.00	-	5 6 10	371-0560-3503
24 / 610	614.20	0.00	0.00	10	5 6	371-0610-3503

Accessories



CLAMP 208



CONNECT 228



CONNECT 270-271



CLAMP 210 BRIDGE CLAMP