

Alu/PVC air conditioning hose, flame resistant

Application

- flexible hose/ ducting for gases
- welding fume extraction
- ventilation, air conditioning, heating system

Properties

- super-light weight

- highly flexible + compressible 10:1
- conforms to RoHS guideline

Temperature Range

- 10°C bis 140°C

Design

- PROTAPE® tape hose

- Pressure max. 250 mm H2O
- Air speed max. 25 m/s
- bending radius 0,6 x ID

Delivery variants

- further diameters and lengths available on request
- black (standard)

I.D.	outer Ø	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(mm)	(kg/m)	(m)	(m)	
3 / 75-76	77.60	0.00	0.00	10	5 6	369-0076-3506
- / 82	84.96	0.00	0.00	10	5 6	369-0082-3506
4 / 100-102	105.00	0.00	0.00	10	5 6	369-0102-3506
4,72 / 120	124.00	0.00	0.00	-	5 6 10	369-0120-3506
5 / 125-127	130.00	0.00	0.00	10	5 6	369-0127-3506
6 / 150-152	155.36	0.00	0.00	10	5 6	369-0152-3506
6,3 / 160	163.40	0.00	0.00	10	5 6	369-0160-3506
7 / 178-180	183.40	0.00	0.00	10	5 6	369-0180-3506
8 / 200-203	206.40	0.00	0.00	10	5 6	369-0203-3506
9 / 228-229	231.40	0.00	0.00	-	5 6 10	369-0228-3506
10 / 254	257.40	0.00	0.00	10	5 6	369-0254-3506
11 / 280	283.40	0.00	0.00	-	5 6 10	369-0280-3506
12 / 305	305.40	0.00	0.00	10	5 6	369-0305-3506
- / 315	318.40	0.00	0.00	10	5 6	369-0315-3506
14 / 356	359.40	0.00	0.00	10	5 6	369-0356-3506
16 / 405-406	409.40	0.00	0.00	10	5 6	369-0406-3506
18 / 457	461.16	0.00	0.00	10	5 6	369-0457-3506
20 / 508	512.20	0.00	0.00	10	5 6	369-0508-3506
22 / 560	564.20	0.00	0.00	-	5 6 10	369-0560-3506
24 / 610	614.20	0.00	0.00	10	5 6	369-0610-3506

Accessories




CLAMP 210 BRIDGE CLAMP



CONNECT 270-271



CLAMP 208



CONNECT 228